

## CLAIMS

1. (Currently Amended) A method for reducing image noise in a scanned image, comprising:
  - decreasing a color level of a color element of a pixel of the scanned image by reducing a number of bits of a full color level of the color element ~~one or more pixels in the scanned image~~ to form a reduced color level image;
  - composing a pattern comprising the color element having less color level than the full color level; and
  - recombining the full color level of the color element ~~the one or more pixels in the scanned image~~ by combining the reduced color level image with the pattern.
2. (Previously Presented) The method of claim 1, wherein the reduced color level image and the pattern are combined using a bit-enhanced method.
3. (Currently Amended) The method of claim 1, wherein combining the reduced color level image with the pattern restores the pixel ~~one or more pixels~~ to include a same number of bits of the color element as before the full color level was decreased.
4. (Previously Presented) The method of claim 1, wherein the pattern comprises a halftone pattern.
5. (Previously Presented) The method of claim 1, wherein the number of bits reduced from the full color level is set to an image noise level.
6. (Currently Amended) A method for reducing noise in an image, comprising:
  - reducing a gray scale an image level of one or more pixels of the image by reducing ~~subtracting~~ a number of bits of gray scale image data from each of the one or more pixels; and

restoring the gray scale image level of the one or more pixels using a halftone pattern comprising a matrix, wherein a number of rows and a number of columns of the matrix correspond to the number of bits of gray scale image data subtracted from the one or more pixels.

7. (Previously Presented) The method of claim 1, wherein the color level of the pattern depends on the number of bits reduced from the full color level.

8. (Currently Amended) A method for reducing noise in an image, comprising:  
reducing a full image level of a color element of a pixel of ~~one or more pixels in the~~ image by decreasing a number of bits of the color element from according to the image noise;  
composing a halftone pattern comprising with a reduced image level of the color element corresponding to the decreased number of bits; and  
recombining an image level of the color element of the pixel ~~one or more pixels in the~~ ~~image~~ using the halftone pattern.

9. (Currently Amended) The method of claim 8, wherein a number of bits of the color element in the recombined image level is the same as a number of bits of the color element in the full image level.

10. (Previously Presented) The method of claim 8, wherein the halftone pattern comprises a matrix having a number of rows equal to the decreased number of bits.

11. (Previously Presented) The method of claim 10, wherein the matrix further comprises a number of columns equal to the decreased number of bits.

12. (Previously Presented) The method of claim 8 further comprising displaying the image including the recombined image level on a computer monitor.

13. (Currently Amended) The method of claim 8, further comprising filling out missing codes of the pixel ~~one or more pixels of the image~~ using a bit-enhanced method.

14 – 17. Cancelled

18. (Currently Amended) An apparatus for reducing noise in an image, comprising:  
means for reducing a full image level of a color element of one or more pixels in the image by decreasing a number of bits of the color element from the one or more pixels, wherein the number of bits corresponds approximately ~~according~~ to the image noise;

means for composing a halftone pattern comprising with a reduced image level of the color element, wherein the reduced image level corresponds ~~corresponding~~ to the decreased number of bits; and

means for recombining an image level of the one or more pixels in the image using the halftone pattern.

19. (Currently Amended) The apparatus of claim 18, wherein a number of bits of the color element in the recombined image level is the same as a number of bits of the color element in the full image level.

20. (Previously Presented) The apparatus of claim 18, wherein the halftone pattern comprises a matrix having a number of rows and columns equal to the decreased number of bits.

21. (Currently Amended) The apparatus of claim 18, wherein recombining the image level restores the one or more pixels to include a same number of bits of the color element as before the full image level was reduced.

22. (Currently Amended) The apparatus of claim 18, wherein the number of bits decreased from the full image level is set to approximate an image noise level.

23. (Currently Amended) The apparatus of claim 18, wherein the reduced image level of the pattern corresponds with ~~depends on~~ the number of bits reduced from the full image level.

24. (Previously Presented) The apparatus of claim 18, wherein one or more of the full image level, the reduced image level, and the image level comprise a color level.

25. (Previously Presented) The apparatus of claim 18, wherein one or more of the full image level, the reduced image level, and the image level comprise a gray level.

26. (New) The method of claim 1, wherein the scanned image comprises three color elements, and wherein the pixel comprises at least one of the three color elements.

27. (New) The method of claim 26, wherein the three color elements comprise a red color element, a blue color element, and a green color element.

28. (New) The method of claim 9, wherein the full image level of the color element and the recombined image level of the color element comprises a gray level.

29. (New) The method of claim 28, wherein the full image level is reduced by decreasing a number of bits of the gray level.